GRAS RA0014-S1

1/2" Electrostatic Actuator for 40AU-1





The GRAS RA0014-S1 1/2" Electrostatic Actuator is for testing the frequency response of the microphone 40AU-1. The GRAS RA0014-S1 can be connected directly to the GRAS 14AA Actuator Supply.



GRAS RA0014-S1 1/2" Electrostatic Actuator for 40AU-1

Technology

Electrostatic actuators are used to simulate the pressure response of condenser microphones. This is done by exerting an oscillating electrostatic force in front of the diaphragm of the microphone and measuring the consequent response of the microphone. These electrostatic oscillations must not reverse polarity if frequency doubling is to be avoided. This is overcome by applying an electrostatic force comprising a sufficiently high polarisation voltage (800 V) upon which a smaller alternating voltage is superimposed.

By applying such an oscillating electrostatic force that sweeps over a range of frequencies from 100 Hz to 200 kHz, the pressure response of the microphone can be tested. To this must be added corrections to determine the microphone's response in a free sound field for various angles of incidence as well its response in a diffuse sound field for random angles of incidence.

Care should be taken when calibrating below 200 Hz because of the influence of pressure equalization in the rear volume of the microphone.

With the <u>GRAS 14AA Actuator Supply</u>, it complies with IEC 61094 -6 "Measurement microphones - Part 6: Electrostatic actuators for determination of frequency responses."

Typical Applications and Use

The RA0014-S1 is used for electrostatic actuator calibration of the microphone 40AU-1.

With the AC test signal superimposed on the 800V DC polarization voltage, the <u>12AA</u> makes it possible to measure the pressure frequency response of the microphone under test.

Its wide frequency range makes it possible to determine the pressure frequency response of condenser microphones from 100 Hz to 200 kHz. For calibration of condenser microphones under 100 Hz, the <u>GRAS 42AE low frequency calibrator</u> is recommended.

A maximum test signal output of 300 V peak to peak allows testing at realistic sound pressure levels.

Compatibility

The RA0014-S1 can be connected directly to the 14AA Actuator Supply.

Quality and warranty

The RA0014 is built to high-quality standards which enables GRAS to offer 3 years warranty against defective materials and workmanship.

Service

Before leaving the factory, all GRAS products are tested. Should a power module become defective, it can be sent to GRAS for repair.



Specifications

ANSI standard		S1.10
IEC standard		61094-6
Weight	g / oz	



Ordering Info

GRAS 14AA	Electrostatic Actuator Amplifier
GRAS AL0010	Actuator Calibration Stand
GRAS RA0067	12-inch Transmitter Adapter
GRAS RA0086	1⁄4-inch Transmitter Adapter

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.grasacoustics.com gras@grasacoustics.com

ΙΙςΔ

GRAS SOUND & VIBRATION

5750 S.W. Arctic Drive Beaverton, OR 97005 Tel: 503-627-0832 Toll Free: 800-231-7350 www.grasacoustics.com sales-usa@grasacoustics.com

АИІН

GRAS SOUND & VIBRATION

Room 303, Building T6 Hongqiaohui, 990, Shenchang Road Minhang District, Shanghai China. 201106 Tel: +86 21 64203370 www.gras.com.cn



ABOUT GRAS SOUND & VIBRATION

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound & Vibration